

UNITED STATES ARMY AVIATION BOARD  
Fort Rucker, Alabama

ATBG-DT-AVN-2360

11 16 NOV 1959

SUBJECT: User Test of Beacon, Light, Pathfinder, Project Nr AB 2059  
and AVN 2360.

TO: President  
United States Army Airborne and Electronics Board  
Fort Bragg, North Carolina

1. Reference is made to:

a. Department of the Army Project Number 8-23-10-110; RDB  
Tech Obj LC-9.

b. Letter, ATBG-AB 2059, Headquarters, US Army Airborne and  
Electronics Board, 19 Aug 1959, subject: "Beacon, Light, Pathfinder."

2. In accordance with your request (reference b above), this  
Board has conducted a series of tests to determine the suitability of  
the Beacon, Light, Pathfinder, for use as a terminal navigation aid to  
Army aircraft.

a. It is concluded that:

(1) The Beacon, Light, Pathfinder in its present con-  
figuration has limited potential as a terminal aid to navigation for  
Army aircraft.

(2) Because of the omni-directional air-to-ground viewing  
feature of the test item, the security of the contemplated operations  
would be compromised.

b. It is recommended that the visible light features of the  
Beacon, Light, Pathfinder, be considered unsuitable as a navigation aid  
for Army aircraft in support of tactical operations.

FOR THE PRESIDENT:

1 Incl  
Extract from Report  
of Test

E. R. WRIGHTMAN  
Capt, AGO  
Adjutant

Approved for public release;  
distribution unlimited.

Copy available to DDC does not  
permit fully legible reproduction

DDC  
RECEIVED  
OCT 15 1976  
RECEIVED

A  
J. J. Peck  
USAAVNTD  
# N675  
AR 34-16 X

COPY AVAILABLE TO DDC DOES NOT  
PERMIT FULLY LEGIBLE PRODUCTION

AD A030733

EXTRACT

US ARMY AVIATION BOARD'S REPORT OF USER

TEST OF BEACON, LIGHT, PATHFINDER

PROJECT NR AVN 2360

\*\*\*\*\*

Date		Time	
BY		BY	
DESCRIPTION		DESCRIPTION	
Dist	AVAIL	Dist	AVAIL
A			

V. TESTS.

1. Physical Characteristics.

a. Weight 29.5 pounds

(1) Telescoping Mast 7.5 pounds

(2) Case containing battery, coding device, light,  
extra lenses 22 pounds

b. Height of telescoping mast

(1) Fully extended 23 feet

(2) Fully collapsed 30 inches

c. Case 18 inches by 9½ inches by 6½ inches.

d. Light - 10 watts, 8 volt provided w/6 - 2 inch OD glass  
hemispherical lenses of red, green, clear, blue, amber, and opaque.

e. Coder - optional automatic or manual selection.

(1) A simple control system allows the light to operate  
automatically and continuously.

(2) The control system further allows selection of con-  
tinuous beam or positions the switches for manual operation for sending  
code.

f. Power Source - 12V nickel-cadmium battery.

Operational Suitability. The Beacon, Light, Pathfinder, was  
erected at two widely separated sites on the Fort Rucker, Alabama, Military  
Reservation. Numerous combinations of lens colors and code signals were  
incorporated on separate tests in an effort to include each lens emission

PG 2

on continuous beam, automatic code, and manually operated code.

a. The basic altitude flown by the Army aviators evaluating the test item was 1,000 feet above the terrain. However, in an effort to insure completeness of test, selected altitudes above and below 1,000 feet absolute were flown.

b. Distances at which light(s) were first visible varied to some degree by the altitude being flown. On clear, moonless nights, while flying at an absolute altitude of 1,000 feet, red, clear, and amber lights were clearly distinguishable at distances up to approximately 10 statute miles. The air-to-ground viewing distance deteriorated, generally, in proportion to the weather conditions except in the case of overcast sky conditions with no precipitation. As sky cover increased, to the exclusion of overhead light, the brilliance of the lights appeared to increase, apparently due to contrast.

c. Discernibleness of color emissions of the test item ranged in effectiveness in order from red, clear, amber, green, to blue. Red emissions were often discernible at the range at which the test item was first attracted to the view of the aviators. When the clear lens was employed simultaneously with other lenses, there was a tendency for the emissions to "spill over" at the expense of the companion lights, often resulting in complete diffusion and blending of all colors when viewed from distances of four miles or more. Blue emissions were seldom visible beyond a range of one and one-half to two miles.

d. The signals emitted from the beacons were readable at somewhat shorter ranges than the extreme limits of air-to-ground viewing limits. The lag between original sighting and readability appears to be geared to adaptability of the observer to signal interpretation. Signal emissions appeared to have the same effect as a flashing beacon in attracting the aviator's attention.

## VI. DISCUSSION.

1. The test item appears to have excellent terminal aid potential under non-tactical conditions. The lights when coded (flashing) were visible and attracted the aviators at ranges in excess of five statute miles and at absolute altitudes of 1,000 feet. Because of the hemispherical design of the lenses, line-of-sight observation was unrestricted as to quadrant. Even when approach headings were varied freely, no difficulty was experienced. In instances wherein several aircraft were converging on the installation site of the test item on divergent headings, the aviators reported "first sightings" and intelligible code at similar ranges and altitudes consistently.

2. Since there is no method of effecting directional emissions of the test item, the advantage accruing from its use as a navigational aid for Army aircraft could be detrimental to the mission of the supported pathfinder unit. In consideration of the use of the test item under tactical

conditions, its demonstrated effectiveness as a navigational aid to Army aircraft is nullified by the abandonment of security control measures of the supported unit. The results of tests have indicated that the emissions of the test item are readily viewable from all quadrants.

\*\*\*\*\*

-----